






Technical requirement:

| | | |
|----|---------------------------------|--|
| 1 | USB Impedance | < 100mΩ |
| 2 | The Force of open the USB Cover | <3000gf |
| 3 | USB Insertion Force | <1000gf |
| 4 | USB Pulling Force | <1500gf |
| 5 | Salt Spray Test | 8H MIN Nacl 5% |
| 6 | Component impart force | 8Kg. f MIN |
| 7 | Temperature resistance | -25° C<T<85° C MIN |
| 8 | TYPE-C | Support various fast charging protocols: DCP / QC3.0 / FCP / AFC / support USB PD protocol |
| 9 | Output-A Port | PD:5V3.1A/ 7V2.4A/9V2A/ 12V1.5A |
| 10 | Output-C Port | USB:FCP/QC2.0/QC3.0/DCP |
| 11 | Power | 36W MAX |
| 12 | Voltage Range | 12V |



Mounting Dimensions

| | | | | | | | |
|-----------|------------|-------------------|--------|----------|--------|--|--|
| Unit | Millimeter | General Tolerance | | | | | |
| Scale | 1:1 | .X±0.5 | ANGLES | | | | |
| Draw | Saint | .XX±0.3 | X.°±5° | | | | |
| Design | Saint | .XXX±0.1 | .X°±3° | | | | |
| Material | | Name | | File No. | | | |
| Weight | | Title | | Page | 1 of 1 | | |
| Draw date | | PROJ. | | REV. | A0 | | |

| | | | | | | | | | | |
|------|----------|--------|---------|----------|---------|--|--|--|--|--|
| **** | ***** | Saint | Saint | **/**/** | Checked | | | | | |
| Mark | Corritor | Revise | Approve | Date | Approve | | | | | |